

Martin Hedley – Speaker

Audio-Visual Requirements

Presentation is in Apple Keynote format, delivered from Martin's personal Apple MacBook Pro. Mr. Hedley brings his own mini-DVI to VGA adapter and power cable with UK format BS 1363 (Type G) plug.

If the MacBook Pro is located away from the speaker, a pit monitor of at least 22" should be available in full sight of the speaker while facing the audience.

The laptop will require 110v or 220v power. Some presentations include sound, so an appropriate sound cable should be available at the podium when appropriate.

A copy of the presentation will be available as back up on USB memory stick.

A wireless lavalier microphone is required and a backup hand held wireless microphone on the podium should be available.

Mr. Hedley moves the slides forward by hand held device. Due to the varying pace of the presentation, it is not possible to cue the slides.

Projection

LCD projector with minimum native resolution of XGA (1024 X 768).

Projector brightness (Lumens rating) should be appropriate for the combination of screen size and audience size.

Screen

The screen should be placed high enough above the floor of the room so that the audience can view the entire screen. At several points in the presentation there is information on the bottom edge of the screen that is very important to the presentation.

Staging

Glass of water or bottle (no ice) on the podium.

Lighting

Lighting should be focused on the speaker if at all possible, and dimmed around the room so that the presentation screen shows in high resolution.